



Providing perspicatis unde omnis iste natus error sit voluptatem accusantium

Network Video Recorders

Video surveillance on board trains



Guaranteed recording availability in all configurations



The great variety of the video recorders product range makes easy the integration in the vehicle whatever is LRV, metro, mass transit or mainline train.

Most specific project requirements can be easily implemented using the configuration capabilities of this equipment.

Faiveley Transport's video recorders are the result of more than 20 years of experience.

XEBRA 3 offers you a large choice of services on ground (real-time, maintenance, geolocalisation...).

JetTransStore allows easy adaptation to existing material (refurbishment).

SuperVision provides great storage capacity and scalability features.

- Vandalism and improper behaviour prevention
- Driving cab monitoring
- Identification of the perpetrators of aggression
- Tracks and signaling systems surveillance



CUSTOMER BENEFITS :

- + Fully user-configurable CCTV system
- + Easy to use thanks to X-TRACK playback station
- + Easy to install
- + Built-to-last and reliable



Typical Characteristics	Xebra 3	JetTransStore	SuperVision
Recording			
Recording format	Proprietary format ensuring video data integrity		
Maximum storage capacity	1 cartridge with 2 disks each (HDD, SSD or combined) Up to 8 To	2 cartridges with 4 disks each (HDD, SSD or combined) Up to 32 To	
Recording modes	Continuous (FIFO), alarm clip only, combined		
Maximum video streams (HD 720p 25 fps) number	12	12	40
Maximum audio streams number	12	12	40
Maximum analogue camera inputs		8	8
Digital inputs/outputs	4 inputs 2 outputs	4 inputs 1 output	4 inputs
Communication ports	1 x RS485/RS422 1 x M12 Ethernet	1 x RS485/RS422/LON 2 x M12 Ethernet 2 x JetStre@m (for retrofit applications)	1 x M12 Ethernet
Download and maintenance	1 x RJ45 Ethernet 1 x USB	1 x RJ45 Ethernet 1 x USB	1 x RJ45 Ethernet
Wireless connectivity			
Built-in modules	GPS, WiFi, NFC tag, 2x4G		GPS
General data			
Input voltage	From 24V to 110V	From 24V to 110V	24VDC or 72-110VDC
Recording temperature	+5°C to +55°C	+5°C to +55°C	0°C to +60°C
Protection	IP20	IP20	IP20
Cooling system	Fanless	Fanless	Fanless
Dimensions	326 x 216 x 85 mm	Rack 2U 19"	Rack 3U 19"
Weight (including the recording media)	5kg	6kg	10kg
Standards	EN 50155, EN 50121-3-2, IEC 61373, EN 60529, EN 45545-2		

To discover everything Wabtec's Network Video Recorders can do, contact:

Faveley Transport Tours

ZI Bois de Plante - Rue Amélia Earhart - BP 43 - 37700 La Ville-aux-Dames - France
 Tel: +33 (0)2 47 32 55 55 - Fax: +33 (0)2 47 32 56 61
 Email: info.cctv@wabtec.com
 www.wabtec.com